

LAS-10 - AIO

LAS-10 Detector - AIO (All-In-One)	
Detection range	> 0,002 mg/l
Airflow	10.000 Ltr/Min or 600 [m³/h] - 2600 gpm or 21.000 [ft³/h]
Reaction time	5-10 sec. depending on preset alarm limit
Gas Detection	Hydrocarbons
Material, enclosure rating	Anodized Aluminum - IP44
Dimensions - Weight	Ø190 x 235mm - 5,5kgs
Power supply	24 Vdc (Internal)
Power consumption	45 W
Operating temperature	-20 ~ +60°C
Operating Humidity	0 - 95% rH
Output Signal	Bi-colored LED
Preset Alarm Levels	Gas Alarm settings 17% or 33% LEL. Mist Alarm setting 5% above actual level of differential Pressure



Power supply / Relay Unit	
Number of detectors	1
Material	Aluminum
Dimensions - Weight	255 x 190 x 90 mm - 3.3 kg
Power supply	Input voltage: 90 - 305 Vac Output voltage: 24 Vdc
Power consumption	5 W
Enclosure rating	IP65
Operating temperature	-20 ~ +70°C
Operating Humidity	0 - 95% rH
Output signals	Alarm/fault relays - RS485/422 Full-duplex

